




# METALLISED POLYESTER CAPACITORS

## MEB-UPS SERIES

**APPLICATION :** In UPS & Inverters.

### TECHNICAL DETAILS

- Dielectric** : Polyethylene Terephthalate
- Electrodes** : Vacuum deposited Zinc Alumimium
- Ref. Standard** : IEC 384-1&2
- Encapsulation** : Plastic box and epoxy (MEB)
- Flame Retardancy** : Conforming to UL 94 V-0
- Environmental** : 55/125/56
- Category**
- Capacitance** :  $\pm 10 \%$
- Tolerance**
- Test Voltage** :  $1.6 \times V_r$  (2 secs.)
- I. R. at 100 V** : 10,000 secs.
- Tan  $\delta$  at 100 KHz** :  $\leq 5.0 \%$



L	P	d
31.0	26.5	0.8

### Dimensions (max. in mm) :

Capacitance mfd.	400 VDC		
	L	B	H
0.68	31.0	8.5	16.0
1.0	31.0	8.5	16.0
1.5	31.0	8.5	16.0
2.0	31.0	11.5	21.0
2.2	31.0	11.5	21.0



**ISO 9001**

## DESAI ELECTRONICS PVT. LTD.

870/5, Bhandarkar Institute Road, Pune : 411 004.

Ph. : 91-20-25654553, 25654554. Fax : 25654273. e-mail : mktg@deccapacitors.net