



METALLISED POLYPROPYLENE SAFETY CAPACITORS

MPS-S SERIES

APPLICATION : In hum-free, step type Electronic Fan Regulator. Premium Quality long life capacitors, with Safety features.

TECHNICAL DETAILS

Dielectric	: Polypropylene (Pattern type)
Electrodes	: Vacuum deposited zinc-aluminium
Voltage	: 250 VAC
Ref. Standard	: IEC 384-16
Encapsulation	: Plastic Box & Epoxy (MPS-S) (Block type - 3-in-1)
Flame Retardancy	: Conforming to UL 94 V-0
Environmental	: 55/105/56
Category	
Capacitance	: $\pm 10 \%$
Tolerance	
Test Voltage	: $1.6 \times V_r$ (2 secs.)
I. R. at 100 V	: $\geq 30,000$ secs.
Dissipation factor	: $\leq 2.5 \%$ at 100 kHz

Dimensions (max. in mm):

Capacitance mfd.	250 VAC		
	L	B	H
1.0, 2.2 & 3.3 (3-in-1)	31.0	30.0	20.5

L	P	d
31	27.5	0.8



ISO 9001

DESAI ELECTRONICS PVT. LTD.

870/5, Bhandarkar Institute Road, Pune : 411 004.

Ph.: 91-20- 25654553, 25654554. Fax : 25654273.e-mail:mktg@deccapacitors.net